

E-Cell MK-3 Stack

Industrial Electrodeionization (EDI) Stacks



Figure 1: E-Cell MK-3 Stack

E-Cell MK-3 is designed to:

- Provide Ultrapure Water for industrial applications including Power, Semiconductor, and General Industry.
- Produce Mixed Bed quality water on a continuous basis.
- Require no caustic or acid for regeneration of ion exchange resin within the stack.
- Be leak free, guaranteed.
- Eliminate brine injection and concentrate recirculation, simplifying system design.

Description and Use

E-Cell MK-3 stacks are electrodeionization (EDI) stacks which use electrical current to deionize and polish reverse osmosis (RO) permeate water. The product water for the MK-3 is at an Ultrapure level required in today's most demanding applications.

Typical Applications

- Microelectronics
- Power Generation (NO_x, Boiler Feed)
- General Industry

Quality Assurance

- CE, UL & CSA marked
- Manufactured in a ISO 9001:2000 facility

MK-3 Stack Specifications		
Nominal Flow	3.4 m ³ /hr	15 gpm
Flow Rate Range	1.7 – 4.5 m ³ /hr	7.5 – 20 gpm
Shipping Weight	92 kg	202 lbs
Dimensions (width x height x depth)	30cm x 61cm x 48cm	12" x 24" x 19"

Typical Performance		
Product Quality		
Resistivity	> 16 MOhm-cm	
Sodium	< 3 ppb	
Silica (SiO ₂) Removal	Up to 99% or < 5 ppb	
Boron Removal	> 95%	
Operating Parameters		
Recovery	Up to 97%	
Concentrate Flow (vs. Product Flow)	Countercurrent, hardness >0.10 ppm as CaCO ₃ Cocurrent, hardness ≤0.10 ppm as CaCO ₃	
Voltage	0 – 300 VDC	
Amperage	0 – 5.2 ADC	
Inlet Pressure	3.1–6.9 bar	45–100 psi
Pressure Drop	1.4–2.8 bar	20–40 psi



Find a contact near you by visiting www.ge.com/water and clicking on "Contact Us".

* Trademark of General Electric Company; may be registered in one or more countries.

©2014, General Electric Company. All rights reserved.

Maximum Feed Water Specifications

Feed Water - Total Exchangeable Anions (TEA as CaCO ₃)	<25 mg/l	<25 ppm
Feed Water - Conductivity, NaHCO ₃ equivalent	< 43 µS/cm	< 43 µS/cm
Temperature	4.4–40°C	40–104°F
Total Hardness (as CaCO ₃)	< 1.0 mg/l	< 1.0 ppm
Silica (SiO ₂)	< 1.0 mg/l	< 1.0 ppm
Total Organic Carbon (TOC as C)	< 0.5 mg/l	< 0.5 ppm
Total Chlorine	< 0.05 mg/l	< 0.05 ppm

Actual performance may vary depending on site conditions.
Reference E-Calc projection software to verify actual performance.
Patents pending.